



DISPENSING SOLUTIONS

AXON A5000

Scalable Solution.

The Axon A5000 fuel dispenser is the most customizable unit of the range with all media/ payment system options available. It represents the perfect choice for those who are looking for an adaptable dispenser that can keep up with the challenges of their business.



Up to 130l / min



Multiple Fuel Types



Up to 5 Fuel Grades



OPT Multimedia



Up to 12 hoses (adblue version)

Maximum efficiency aligned with a great user experience.

SOLID CONSTRUCTION FRAME

Frame:
galvanized steel with double coated painting
Housing:
stainless steel
Image Panels:
aluminium with double coated painting

PARTIAL AND FULL RETRACTION

Hoses designed for an easy handling.

MINIMALIST DESIGN

The sharp lines and darken colours ensure a clean appearance, keeping it free of dirt and wear signs.

TOUCHSCREEN WITH A MODERN LOOK AND FEEL

With tempered glass for direct digital print on glass for enhanced usability and greater user experience.

MODULAR PAYMENT MODULE

Allows multiple payment configurations (OPT or standalone media display) and integrates with third-party systems.

EASIER MAINTENANCE AND SERVICEABILITY

The new panels combined with greater depth in the interior provide practical access to all the regulation components when necessary, which is key for easier maintenance.



Certificate: ATEX | MID

AXON A5000

Durable and larger display



- Crisp digits under any lighting conditions
- Maximum flexibility with minimalist design
- Intuitive touchscreen

Enhanced hydraulics



- Aluminum alloy obtained through injection under pressure
- Inlet suction lines aligned for the entire range
- Meter without mechanical calibration
- P-Flux connected to electronics for error management
- Quick coupling connection for the meter



✓ TECHNICAL SPECS

ADMISSION	Suction: High Performance Compact Gear Pump PPS Pressure: Submersible Pump	HOSE	Ø16, 19, 21, 25 mm (EN1360/EN13483) (VR2 approved)
METER	Positive displacement meter, with pulse generator	NOZZLE	Automatic ZVA2 or others
FILTERS	Reusable stainless steel, 100 µm mesh	FLOW RATES	10, 40, 80, 130 l/min
MOTOR	Eexd, single/three-phase, 50/60 Hz w/ internal thermal protection	COMMUNICATION PROTOCOLS	Petrotec, EP55, Pulse Interface, ER3, IFSF IP, IFSF Lon, HDX 485 and HDX 2WI (Gilbarco), Dunclare, Pumalan, HDX IP (Tesco)
CALCULATOR	iMC	DISPLAY	Touchscreen • Tempered Glass • Volume and amount preset
OPTIONS	Speed Selector • Voice Module • Electro-mechanical Totalizers • Circuit Breaker • Main Safety Switch (LPG) • Electronics Head Heating • Vapour Recovery Stage II • Vapour Recovery with Monitoring • Single /Three-Phase Motor • AdBlue Hydraulic Housing Heating (ATEX) (1) • Adblue hydraulic housing heating (1) (2) • Satellite ready (1 per side) • Breakaway couplings • Custom Nozzles and satellite • Flexible Riser Connection • Foundation Frame • Stainless Steel AISI316 housing • OPT (3) • Multimedia		



(1) Only available with Full Retraction; (2) Only available with 1P version; (3) Integration with a wide range of terminals.

> DIMENSIONS

A5000 HH PARTIAL RETRACTION



A5000 LH COMPLETE RETRACTION



www.petrotec.com

© 2024 Petrotec Group | All rights reserved. Petrotec, the Petrotec logo, Axon and combinations thereof are registered trademarks of Petrotec Group. Other names are informational and may be trademarks of their respective owners. Petrotec is continuously improving its products. Changes on the specifications may occur without prior notice. The imagery used may be indicative of style only. The available brochures are a guide and do not constitute an offer or contract.

